

Technical Data Sheet

AtlasFloor

Color Sand Self Leveling

Product Description

A solvent-free epoxy, colored-sand self-leveling floor coating designed to create decorative patterns and colors. The source sheet describes a seamless finish for commercial, industrial and residential floors.

Product Information

System	: Solvent-free epoxy, colored sand
Components	: 2 (Part A and Part B)
Appearance in container	: Mix uniformly; no hard lumps
Density	: 1.70 g/mL

Application Information

Mixing Ratio	: A:B = 6:1 (basis not stated)
Packing	: 1.5 kg, 3.5 kg and 7 kg per set

Benefits

Seamless decorative appearance: An integrated surface with a choice of color and pattern effects.

Wear and pressure resistance: Designed for areas subject to frequent use, with a surface that is easy to clean and maintain.

Application Area

Commercial premises: Shopping malls, exhibition halls and offices. **Industrial environments:** Plants and warehouses. **Residential interiors:** Decorative floor areas.



COLY COATING SDN BHD

No. 421-B Batu 14, Jalan Kapar, 42200 Kapar, Klang, Selangor

Tel: +603 3259 3905 | enquiry@colycoating.com | www.colycoating.com

Technical Data Sheet

AtlasFloor

Color Sand Self Leveling

Application & Performance Information

Property	Value
Table drying time, ≤	2 hours
Practical time, ≤	24 hours
Hardness, ≥	H
Water resistance	0.50 [unit not stated]
Wear resistance (750 g / 500 r), ≤	172 h [unit appears inconsistent]
Packing	1.5 kg, 3.5 kg and 7 kg per set

Technical values are transcribed from the supplied AtlasFloor 2025 sheet; packing sizes were updated as instructed. Confirm the test method, units, cure conditions, mixing-ratio basis and the water/wear-resistance entries with the technical team before external issue.

Safety Precautions

Avoid contact with skin and eyes. If material contacts skin, wash with water and a suitable cleanser. If it enters the eyes, rinse with plenty of water and seek medical attention. Use with good ventilation. Keep away from smoking, sparks and ignition sources. Follow site health and safety requirements.

Packing & Storage

Packing: 1.5 kg, 3.5 kg and 7 kg per set. **Storage:** Store in a cool, dry place away from heat and ignition sources, at 5-35°C. Protect from freezing. The supplied sheet states a 12-month storage period; check suitability before use after this period.

Technical Note

This sheet adapts the supplied product information into the Coly Coating TDS layout. Performance and application data require confirmation against current product testing. Test suitability for the intended substrate and service conditions before use.

Prepared from the supplied AtlasFloor 2025 TDS (source revision: Dec 2025). Layout adaptation: 28 Sep 2026.

